
Cutting .090" TYPE 27 Depressed Center Wheels



A60S

- Thin .090 width
- Special aluminum oxide grain
- Hard bond for extremely long life
- **Excellent for notching and cutting**



METAL Ferrous and/or non-ferrous metals (iron, steel, welds, etc.)

Size A Dia.	Size B Width	Size C Bore	Max RPM	Part Number	Qty Per Box	Qty Per Ctn	Lbs Per Box
4	.090	5/8	19,000	20902	25	100	4
4-1/2	.090	7/8	13,300	20903	25	100	4
4-1/2	.090	5/8-11	13,300	20913	10	40	5
5	.090	7/8	12,200	20904	25	100	6
5	.090	5/8-11	12,200	20914	10	40	5
6	.090	7/8	10,200	20905	25	100	8
6	.090	5/8-11	10,200	20915	10	40	7
7	.090	7/8	8,500	20906	25	100	14
7	.090	5/8-11	8,500	20916	10	40	11
9	.090	7/8	6,600	20909	25	50	21
9	.090	5/8-11	6,600	20919	10	40	11

Patented !




SaitZ-tech™

- Tough zirconium grain
- **High performance cutting and notching for the toughest applications**

METAL Ferrous metals (iron, steel, welds)

STAINLESS Stainless steel, high tensile alloys



Size A Dia.	Size B Width	Size C Bore	Max RPM	Part Number	Qty Per Box	Qty Per Ctn	Lbs Per Box
4	.090	5/8	19,000	20942	25	100	4
4-1/2	.090	7/8	13,300	20943	25	100	4
4-1/2	.090	5/8-11	13,300	20953	10	40	5
5	.090	7/8	12,200	20944	25	100	6
5	.090	5/8-11	12,200	20954	10	40	5
6	.090	7/8	10,200	20945	25	100	8
6	.090	5/8-11	10,200	20955	10	40	7
7	.090	7/8	8,500	20946	25	100	14
7	.090	5/8-11	8,500	20956	10	40	11

Note: Reusable 5/8-11 adaptor for use on Type 1 and Type 27 reinforced wheels with a 7/8 arbor, a max. diameter of 5" and a wheel thickness of .045 to 1/8" available on page 153 (part #95055)



Angle Grinder

Tech INFO

- Unique, thin Type 27 shape can be used on all angle grinders in accordance with ANSI B7.1
- Special bond formulation offers the fastest cutting, longest lasting thin wheels
- Externally reinforced with fiberglass layers to provide ultimate safety in a thin wheel