TYPE 1
Thin High Speed Cut-off Wheels

Cutting




Die Grinder



A24R - *General Purpose*

- Aluminum oxide grain
- General purpose, **long life**

METAL Ferrous metals (iron, steel, welds, etc.)



For items A36T, A60S, and A60T see descriptions on page 46

Size A Dia.	Size B Width	Size C Bore	Max RPM	Grades Available Part Numbers A24R	A36T	A60S	A60T	Qty Per Box	Qty Per Ctn	Lbs Per Box
2	1/16	1/4	30,558	-	23004	-	23005	50	50	1
2	1/16	3/8	30,558	-	23002	-	23003	50	50	1
2	.035	1/4	30,558	-	23012	-	23013	100	100	1
2	.035	3/8	30,558	-	23010	-	23011	100	100	1
2-1/2	1/16	1/4	24,446	-	23022	-	23023	50	50	2
2-1/2	1/16	3/8	24,446	-	23020	-	23021	50	50	2
2-1/2	.035	1/4	24,446	-	23032	-	23033	100	100	2
2-1/2	.035	3/8	24,446	-	23030	-	23031	100	100	2
3	1/16	1/4	25,000	-	23042	-	23043	50	50	3
3	1/16	3/8	25,000	-	23040	-	23041	50	50	3
3	.035	1/4	25,000	-	23052	-	23053	100	100	3
3	.035	3/8	25,000	-	23050	-	23051	100	100	3
3	1/8	3/8	20,372	23060	-	-	-	25	100	2
4	1/16	1/4	19,000	-	23067	-	23068	50	50	5
4	1/16	3/8	19,000	-	23065	-	23066	50	50	5
4	1/16	5/8	19,000	-	23061	-	23062	50	50	5
4	.035	1/4	19,000	-	23071	-	23072	100	100	5
4	.035	3/8	19,000	-	23069	-	23070	100	100	5
4	.035	5/8	19,000	-	23063	-	23064	100	100	5
4	.045	5/8	19,000	-	-	23099	-	50	200	4
4	1/8	3/8	15,278	23075	-	-	-	25	100	4




Saitech Ultimate Performance™

- High performance, ceramic aluminum oxide grain
- **Very uniform, high density grain structure is extremely durable and self sharpening for long life and cooler cut**
- **High Performance**
- Combines **fast cutting with extremely long life**

STAINLESS Stainless steel, high tensile alloys

METAL Ferrous and/or non-ferrous metals

1/4" shank adaptors available on page 153



Size A Dia.	Size B Width	Size C Bore	Max RPM	Part Number	Qty Per Box	Qty Per Ctn	Lbs Per Box
3	1/16	1/4	25,000	23142	50	50	2
3	1/16	3/8	25,000	23140	50	50	2
3	.035	1/4	25,000	23152	100	100	3
3	.035	3/8	25,000	23150	100	100	3
4	1/16	1/4	19,000	23167	50	50	4
4	1/16	3/8	19,000	23165	50	50	4
4	1/16	5/8	19,000	23161	50	50	4
4	.035	1/4	19,000	23171	100	100	5
4	.035	3/8	19,000	23169	100	100	5
4	.035	5/8	19,000	23163	100	100	5

Tech INFO

- Type 1 shape for square, burr-free cutting
- Patented 3M™ Cubitron™ grain formulation outlasts standard aluminum oxide wheels
- Externally reinforced with fiberglass layers to provide ultimate safety in a thin wheel

3M and Cubitron are trademarks of 3M